




BACK-LIT LED PANEL LIGHT



PRODUCT OVERVIEW

The back-lit LED panel light give a beautiful, uniform and soft light on the surface.

The lens on the LEDs distribute the LED light even and with anti-glare. This panel light is adapted back-lit technology, it won't get yellowing after using long time period.

The outer frame is made of aluminum alloy by anodizing, and light source is LED. The frame is simple and luxurious. The whole light has good lighting effects and can bring people the feeling of beauty.

KEY FEATURES

- Wattage and CCT tunable.
- PMMA lenses over LEDS/PS diffuser
- High lumen efficient 125lm/w.
- Embedded and Suspending mounting.
- ETL,DLC5.1 listed.
- 5 years warranty.
- Full series:2*2FT,2*4FT,1*4FT.
- High quality powder coating board, rust against.
- 0-10V dimmable in standard configuration.


APPLICATION

- Office/shool
- Subway&train station
- Supermarket,etc

PERFORMANCE SUMMARY

| Construction & Materials | | |
|--------------------------|---|-----------------------------------|
| Diffuser | Acrylic lens and PS cover | |
| Housing | Powder coating rust against Sheet Metal Board & 6063 Aluminum Frame | |
| Finish | Pure White | |
| Environmental System | | |
| Work Environment | Suitable for dry and damp location | |
| Operating Temperature | -20°C to 45°C | |
| Parameter | | |
| CRI | >80 | |
| Efficacy | 125lm/w-140lm/w(125lm/w on average) | |
| CCT | Single color:3000K,3500K,4000K,5000K,5700K,6500K 3CCT tunable:4000K-5000K-6500K/3000K-4000K-5000K 5CCT tunable:3000K-4000K-5000K-5700K-6500K | |
| Input Voltage | 100-277Vac or 100-347Vac; 50/60HZ | |
| Wattage | 2*2FT single 40W 3 wattages selectable:40w/30w/20w 5 wattages selectable:40w/35w/30w/25w/20w | |
| | 1*4FT single 50w 3 wattage selectable:50w/40w/30w 5 wattage selectable:50w/45w/40w/35w/30w | |
| | 2*4FT single 50W or 60W or 72W 3 wattage selectable:50w/40w/30w 3 wattage selectable:60w/50w/40w 5 wattage selectable:60w/55w/50w/45w/40w 5 wattage selectable:72w/60w/50w/45w/40w | |
| Dimming | 0-10V dimming | |
| Certification | cETLus,DLC 5.1 | |
| Emergency | Input voltage | 100-277Vac or 100-347Vac; 50/60HZ |
| | Battery type | Li-ion battery |
| | Output power | 8W/15W/20W |
| | Charge time | >24hrs |
| | Emergency time | >1.5hrs (90min) |

INSTALLED OPTIONS

| IMAGE | MODEL NUMBER | DESCRIPTION |
|---|--------------|----------------------------|
|  | MC-SMK14 | 1'*4' surface mounting kit |
| | MC-SMK24 | 2'*4' surface mounting kit |
| | MC-SMK22 | 2'*2' surface mounting kit |

ORDERING GUIDE

P/N.:MC-BPXF-XXXXX

The first“X”can be any two letters to represent lamp size:22=2*2FT ,14=1*4FT ,24=2*4FT;


The second”X”can be any one letter to represent lamp wattage:40=40w,40=40w/30w/20w wattage tunable;40=40w/35w/30w/25w/20w wattage tunable;50=50w,

50=50w/40w/30w wattage tunable;60=60w,60=60w/50w/40w wattage tunable,72=72w;72=72w/60w/50w/45w/40w wattage tunable;


The third "X" can be any one letter to represent lamp color temperature: A=3000k, B=3500k, C=4000K, D=5000K, E=6500K, H=5700K, I=4000k/5000k/6500K CCT tunable; K=3000k/4000k/5000k CCT tunable, L=3000k/4000k/5000k/5700k/6500k
 The fourth "X" can be any one letter to represent the lamp is single color temperature, CCT and power tunable or power tunable only: S=single color, D=CCT and power tunable, P=power tunable
 The fifth "X" can be any one letter to represent the emergency lamp or not: blank=emergency model, N=non-emergency model;
 The sixth "X" can be any one letter to represent the input voltage: blank=100-277Vac, A=100-347Vac

| P/N | Order Item No.: | Description |
|----------------|-----------------|---|
| MC-BP22F-40IDN | 1996 | 2*2FT, 3CCT :4000k/5000K/6500K, 3 wattage :40w/30w/20w |
| MC-BP24F-60KDN | 1997 | 2*4FT, 3CCT :3000k/4000k/5000k, 3 wattage:60w/50w/40w |
| MC-BP24F-72ESN | 1816 | 2*4FT, single 72W, 6500K |
| MC-BP24F-72LDN | 2010 | 2*4FT, 5CCT :3000K/4000k/5000k/5700k/6500k, 5 wattage:72w/60w/50w/45w/40w |
| MC-BP14F-50IDN | 929 | 1*4FT, 3CCT:4000k/5000k/6500k, 3 wattage:30w/40w/50w |


CUT SHEET



DIMENSIONS



PACKAGING INFORMATION



| Model | Packing Detail | | | | |
|-------|----------------|-------|-------|--------|--------|
| | L(cm) | W(cm) | H(cm) | PC/CTN | GW(Kg) |
| 2'×2' | 66 | 27 | 68 | 6PC | 15.2 |
| 1'×4' | 127 | 27 | 37 | 6PC | 14.6 |
| 2'×4' | 129 | 20 | 68 | 4PC | 18.9 |